


DROP Fiber Optic cable FTTx up to 12F

Self supporting fiber optic cable for indoor or outdoor use



- PU / LSZH Jacket
- Aramid yarn
- Tight buffer fibre (250mic)

Application:

Jacket:

DROP PU	DROP LSZH
Indoor / Outdoor	Indoor / Outdoor
PU	LSZH Black UV stabile
2f-6f : Ø 3,0mm 8f-12f : Ø 3,4mm	

Fibre

SM 9/125 ITU-T G657A
red, green, blue, yellow, white, grey, brown, violet, turquoise, black, orange, pink

Strength member:

Temperature range

Aramid yarn
Installation -5°C to +40°C
Operation -20°C to +60°C
Storage -25°C to +60°C

Crush resistance

Min. bend radius (ft)

Min. bend radius (st)

Max. tensile strength

Max. cable length

Weight

500N/10cm	
23mm	
12 mm	
530 N	500N
4100m	
2-6f : 8,5kg/km 8-12f : 10kg/km	2-6f : 10kg/km 8-12f : 12kg/km

Advantages:



AERIAL



HIGH FLEXIBILITY



FLAME RETARDANT



ULTRAVIOLET RESISTANCE



MOISTURE PROTECTED



100% TOTALLY DIELECTRIC